

ASUSTOR Data Master


New Features of ADM 4.0



Upgraded SAMBA

Samba has been upgraded to version 4.12 for increased performance.

- Up to 5% increased performance
- Improved compatibility with Windows devices and Time Machine



Upgraded Security with OpenSSL

Updated OpenSSL brings improved security for SAMBA, FTP, Rsync and web servers. OpenSSL updates also bring improved performance and compatibility, ensuring that encrypted connections are both fast and safe.




Brand New Login Page

Login page now be customized. Move around the login details dialogue box, change wallpaper and switch between light and dark modes for an unmatched custom experience. Add important system announcements to notify employees of various events.



Web Center

Easily set up a website with Web Center. Install Apache or Nginx or almost any other web server implementation and add multiple website portals for an easy-to-use web server experience.



Brand New Dark Mode

Save energy and preserve the life of OLED panels with the all-new Dark Mode for ADM.



New Theme Options

ADM has expanded its customizability with all new themes. Create custom themes by changing wallpaper, icons and colors to make your NAS truly yours.



All-New Task Monitor

The all-new Task Monitor displays even more information than ever before, giving you total control.



ASUSTOR Searchlight

Searchlight brings enhanced search that also shows file information and previews of pictures and videos.

Business

Comprehensive Backup Solutions: Centrally Backup and Manage Data from Different NAS Models and Brands

- Your data backup center for Windows and Mac
- Internal backup completely utilizes SATA's full speed
- Internal backups + MyArchive =
Offsite data protection + Unlimited storage capacity expansion
- Use FTP, Rsync for two-way backup and secure data transfers
- Use DataSync Center for two-way backup to another ASUSTOR NAS through EZ Sync
- Backup and restore phone data with AiData and AiFoto 3
- Back up to cloud services easily with Cloud Backup Center or DataSync Center. Supports Amazon S3, Azure, Google Drive, HiDrive, Dropbox, OneDrive and more
- USB One Touch backup or backup to the ASUSTOR AS6004U

Virtualization Ready

Complete iSCSI/IP-SAN and NFS support.
VMware, Citrix and Hyper-V ready.

Ransomware recovery - Snapshot Center

ASUSTOR NAS devices support snapshots on Btrfs volumes and iSCSI volumes, ensuring that if ransomware attacks, changes are reversible

Evolved Network Defender

- Block brute-force attacks with the automatic blacklist
- Trust List can prevent trusted IP addresses from being automatically blocked in the event of too many inadvertent login failures
- The Blacklist and Whitelist can be defined by specific IPs, IP ranges, and geolocation

Seamless integration with AD, ACL and LDAP

LDAP and Windows AD support combined with ACL allows IT professionals to use the permissions and security settings in Windows to quickly configure shared folder access rights for users and groups on an ASUSTOR NAS. These settings can be applied to Samba, File Explorer, AFP, NFS, or WebDAV allowing businesses to maintain flexibility and security with regards to data access

EZily connect to your NAS with EZ-Connect and EZ-Connect.to

Easily connect remotely to your NAS even in network environments with multiple routers from within the network. ASUSTOR's EZ-Connect supports a variety of features, including, but not limited to Internet passthrough and remote shared folder mounting on Windows Explorer. EZ-Connect.to uses a web browser to connect to a NAS remotely and access data. Sign up for an ASUSTOR cloud ID and append it to the URL followed by a dot and ezconnect.to to access data on your NAS anytime and anywhere with an internet connection.

Surveillance Center

Instant Notifications

Surveillance Center supports push notifications, emails and SMS messages to individual cameras and events. When an event occurs, Surveillance Center will send out a notification according to its settings.

Local HDMI Output

Connect your NAS to an HDMI monitor or HDTV and Surveillance Center provide high resolution video feeds through ASUSTOR Portal. Directly search and play back specific recording files using the timeline or calendar and listen to live audio as well.



Centralized Surveillance Software - CMS Lite

A solution designed for systems with multiple servers spread across different locations, CMS Lite allows surveillance professionals to have more flexibility and convenience when monitoring and playing back video. Manage up to 128 IP cameras and ASUSTOR NVRs in up to 32 different locations, significantly enhancing management efficiency.

Automated Event Action Rules

Automated event action rules allow administrators to customize alarm handling rules. When an event occurs, your NAS can select different measures to handle a situation based on the type of event or the time the event occurred.



Cross-Browser Support

Receive 4 free camera channel licenses, the most in the industry

Use virtually any browser on Windows and macOS for seamless operation.

*Supports Chrome, Microsoft Edge, Mozilla Firefox on Windows and Safari and Mozilla Firefox on macOS



Smart Passive & Active Recording Modes

Surveillance Center provides a variety of passive and active recording modes, no matter if you require scheduled recording for a specific time period or recording only once an event has occurred, Surveillance Center is able to meet your needs.



Multi-Stream

Surveillance Center supports 3 independent video streaming modes*, allowing administrators to configure default resolutions for recordings and viewing feeds remotely. Select resolutions based on network bandwidth and the number of channels that they are viewing, optimizing video streaming under different network bandwidth limitations.

*Number may vary according to camera brand.



Lifestyle Applications

01

The Dynamic ASUSTOR Portal

Connect your NAS to your TV via HDMI and immediately access ASUSTOR Portal. Further combine it with an audio amplifier and experience the crystal clear sound of high resolution multi-channel audio. Get ready to enjoy your favorite digital entertainment like never before.



02

Your Dedicated Cinema: LooksGood

LooksGood is a dedicated video management center web-based video player. Compatible with the most popular web browsers, enable the LooksGood app from within ADM to begin playing high definition videos. LooksGood 2.0 features a stylish and modern UI that displays video collections using thumbnails and a poster wall layout for easy browsing. Furthermore, enhanced smart database management now provides global searches providing more speed and efficiency. LooksGood also supports Chromecast, DLNA and Apple TV using AiVideos, allowing you to stream your videos to the big screen and share them with friends and family.

Photo Gallery 3 Brings Smart Albums and Smart Photo Management

Organize, share, collect and view photos easier than before with Photo Gallery 3. Photo Gallery 3 is now able to select any shared folders on a NAS as a media source to easy importing. Photo Gallery 3 introduces new timeline and multiple album viewing, smart albums, general albums, shared albums and also introduces albums that shared by friends and family making it easier to relive your best memories again and again. Photo Gallery 3 also introduces support for location recognition, ensuring that you no longer forget the place that awesome waterfall resides. After uploading photos to a NAS, Photo Gallery 3 automatically helps organize photos, making large album management easier than ever.



03

Ultimate Audio Enjoyment with SoundsGood

Easily create an online streaming music platform with SoundsGood to play your favorite pop songs or timeless classical pieces from the music collection on your NAS. With dual-mode streaming, you can choose to play music to your web browser or mobile device to enjoy music by yourself or play your music locally from the NAS. Connect to devices from your NAS to HDMI amplifiers or USB/Bluetooth speakers to allow you to play music for friends and family.



04

ASUSTOR Live

Your own streaming center. Stream your from a phone or tablet as well as a computer to multiple streaming platforms, including, but not limited to YouTube, Twitch, Facebook, Instagram, Restream or RTMP compatible platforms. Unlike services like restream.io, ASUSTOR Live doesn't require fees to operate to stream to multiple platforms and channels which saves you money and streaming resources. Recordings can be safely saved to your NAS for future use.



05

06

WOW (Wake on WAN), Always on Standby

Exclusive

WOW (Wake-On-WAN) maximizes the access flexibility of your NAS. Using ASUSTOR's dedicated mobile app, you will be able to wake your NAS that is in sleep mode or powered off. Even if you are on an external network you will be able to enable all services on your NAS at any time. WOW truly redefines power saving and convenience on your NAS.

*Supported Models:

AS52/53/63/64/Drivestor/Drivestor Pro/Lockerstor series



Mobile Apps

AiMaster



Initialize a NAS easily without a PC by using AiMaster on a phone to set up and manage your NAS. No matter if it is adding new users, creating shared folders, remote wake-up, installing exciting new NAS apps, upgrading your firmware or checking the real-time status of your system, AiMaster helps you get it done with ease.



AiData

Get access to your data on your NAS from the convenience of your mobile device with ASUSTOR's AiData mobile app. AiData allows you to manage all the files on your NAS.

AiDownload



Use your Android device to search for torrents and easily add downloads to Download Center on your NAS. Easily monitor current downloads, establish new downloads and RSS feeds and instantly receive push notifications for completed downloads on your Android phone or tablet.



AiFoto 3

The all new AiFoto 3 has been revamped and brings a variety of new features to make photo organization easier than ever. New features for AiFoto3 include, but not are limited to timelines, smart albums. Performance enhancements, support for HEIC images and custom share links make for an even better photo viewing and sharing experience.

AiMusic



AiMusic allows you to stream music from your NAS to your mobile device. Effortlessly select songs from different genres in an organized music library or even download entire playlists to your mobile device for offline listening. Enabling random playback allows you to create a random playlist at any time. Now no matter where you are, you'll always have your music with you.



AiVideos

AiVideos supports real-time transcoding, enabling a high resolution video streaming experience by selecting the video of your choice from the app. AiVideos also supports Chromecast and Apple TV, allowing you to stream your videos to the big screen and share them with friends and family.

AiRemote



Control ASUSTOR Portal without a keyboard and mouse. From navigating the media player menus to controlling video playback and adjusting volume, AiRemote makes it easy. Additionally, AiRemote provides touchpad and keyboard modes when using the included browser.



AiSecure

AiSecure allows you to effortlessly keep an eye on your most valued assets. In addition to monitoring live surveillance feeds, push notifications can be sent immediately to your mobile device in the event of any disruptions, allowing you to keep watch over your personal property.

Hardware Specifications

Personal to Home

| |  DRIVESTOR 2 AS1102T |  DRIVESTOR 4 AS1104T |  DRIVESTOR 2 Pro AS3302T |  DRIVESTOR 4 Pro AS3304T |
|-------------------|---|---|--|---|
| Processor | Realtek RTD1296 1.4 GHz Quad-Core Processor | Realtek RTD1296 1.4 GHz Quad-Core Processor | Realtek RTD1296 1.4 GHz Quad-Core Processor | Realtek RTD1296 1.4 GHz Quad-Core Processor |
| Memory | 1GB DDR4 (non-upgradeable) | 1GB DDR4 (non-upgradeable) | 2GB DDR4 (non-upgradeable) | 2GB DDR4 (non-upgradeable) |
| Drive Bays | 2x 3½" SATA III | 4x 3½" SATA III | 2x 2½"/3½" SATA III | 4x 2½"/3½" SATA III |
| M.2 | — | — | — | — |
| USB | 2x USB 3.2 Gen 1 | 2x USB 3.2 Gen 1 | 3x USB 3.2 Gen 1 | 3x USB 3.2 Gen 1 |
| LAN | 1x 2.5-Gigabit (Wake On WAN) | 1x 2.5-Gigabit (Wake On WAN) | 1x 2.5-Gigabit (Wake On WAN) | 1x 2.5-Gigabit (Wake On WAN) |
| Expansion | — | — | — | — |
| Dimensions(HxWxD) | 165x102x218 mm | 165x164x218 mm | 170x114x230 mm | 170x174x230 mm |
| Weight | 1.14kg/2.5lb | 1.57kg/3.45lb | 1.6kg/3.53lb | 2.2kg/4.85lb |
| Power | 65W AC Adapter | 90W AC Adapter | 65W AC Adapter | 90W AC Adapter |
| Operation | 11.6W | 22.8W | 12.3W | 23.1W |
| Disk Hibernation | 5.97W | 9.41W | 6.04W | 10.1W |
| Sleep Mode (S3) | No Sleep Mode | No Sleep Mode | No Sleep Mode | No Sleep Mode |
| Volume Type | Single, JBOD, RAID 0/1 | Single, JBOD, RAID 0/1/5/6/10 | Single, JBOD, RAID 0/1 | Single, JBOD, RAID 0/1/5/6/10 |
| Display Out | — | — | — | — |
| Infrared Receiver | — | — | — | — |
| Service LED | — | — | — | — |
| Disk Tray Lock | — | — | — | — |
| LCD Panel | — | — | — | — |

Home to Power User

Power User to Business



AS5202T



AS5304T



LOCKERSTOR 2
AS6602T



LOCKERSTOR 4
AS6604T

| | AS5202T | AS5304T | LOCKERSTOR 2 AS6602T | LOCKERSTOR 4 AS6604T |
|-------------------|---|--|--|--|
| Processor | Intel Celeron J4025 Dual-Core 2.0GHz (burst up to 2.9GHz) | Intel Celeron J4125 Quad-Core, 2.0GHz up to 2.7GHz | Intel Celeron J4125 Quad-Core, 2.0GHz up to 2.7GHz | Intel Celeron J4125 Quad-Core, 2.0GHz up to 2.7GHz |
| Memory | 2GB DDR4-2400 SO-DIMM (Expandable. max. 8GB, 4GB x2) | 4GB DDR4-2400 SO-DIMM (Expandable. max. 8GB, 4GB x2) | 4GB DDR4-2400 SO-DIMM (Expandable. max. 8GB, 4GB x2) | 4GB DDR4-2400 SO-DIMM (Expandable. max. 8GB, 4GB x2) |
| Drive Bays | 2x 2½"/3½" SATA III | 4x 2½"/3½" SATA III | 2x 2½"/3½" SATA III | 4x 2½"/3½" SATA III |
| M.2 | — | — | 2x M.2 PCIe (NVMe) Support M.2 2280 | 2x M.2 PCIe (NVMe) Support M.2 2280 |
| USB | 3x USB 3.2 Gen 1 (1x Front ; 2x Rear) | 3x USB 3.2 Gen 1 (1x Front ; 2x Rear) | 3x USB 3.2 Gen 1 (1x Front ; 2x Rear) | 3x USB 3.2 Gen 1 (1x Front ; 2x Rear) |
| LAN | 2x 2.5-Gigabit (Wake On WAN) | 2x 2.5-Gigabit (Wake On WAN) | 2x 2.5-Gigabit (Wake On WAN) | 2x 2.5-Gigabit (Wake On WAN) |
| Expansion | — | — | — | — |
| Dimensions(HxWxD) | 170x114x230 mm | 170x174x230 mm | 163.5x108x230 mm | 185.5x170x230 mm |
| Weight | 1.6kg/3.53lb | 2.2kg/4.85lb | 2 kg/4.4 lb | 2.96 kg/6.5 lb |
| Power | 65W AC Adapter | 90W AC Adapter | 65W AC Adapter | 90W AC Adapter |
| Operation | 17W | 27W | 15.9W | 27.6W |
| Disk Hibernation | 10.5W | 12.6W | 9.2W | 12.6W |
| Sleep Mode (S3) | 1.3W | 1.4W | 0.66W | 0.75W |
| Volume Type | Single, JBOD, RAID 0/1 | Single, JBOD, RAID 0/1/5/6/10, RAID 1/5 + Hot Spare | Single, JBOD, RAID 0/1 | Single, JBOD, RAID 0/1/5/6/10, RAID 1/5 + Hot Spare |
| Display Out | 1x HDMI 2.0a | 1x HDMI 2.0a | 1x HDMI 2.0a | 1x HDMI 2.0a |
| Infrared Receiver | Yes | Yes | Yes | Yes |
| Service LED | — | — | — | — |
| Disk Tray Lock | — | — | Yes | Yes |
| LCD Panel | — | — | — | Yes |

Power User to Business

Expansion Units



LOCKERSTOR 8
AS6508T



LOCKERSTOR 10
AS6510T



LOCKERSTOR 10 Pro
AS7110T



AS6004U

| | LOCKERSTOR 8 AS6508T | LOCKERSTOR 10 AS6510T | LOCKERSTOR 10 Pro AS7110T | AS6004U |
|-------------------|--|--|--|--|
| Processor | Intel ATOM C3538 2.1GHz Quad-Core | Intel ATOM C3538 2.1GHz Quad-Core | Intel 9 th generation Quad-Core Xeon 4.6GHz Turbo | External Ports USB 3.2 Gen 1 Type B |
| Memory | 8GB SO-DIMM DDR4 (Expandable. max. 64GB, 32GB x2) | 8GB SO-DIMM DDR4 (Expandable. max. 64GB, 32GB x2) | 8GB ECC DDR4-2666 SO-DIMM (Expandable. max. 64GB, 32GB x2) | Maximum Internal Raw Capacity 72TB (4x 18TB HDD) |
| Drive Bays | 8x 2½"/3½" SATA III | 10x 2½"/3½" SATA III | 10x 2½"/3½" SATA III | Drive Bays 4x 2½"/3½" SATA III |
| M.2 | 2x M.2 PCIe (NVMe) or SATA SSD Support M.2 2280, 2260 and 2242 | 2x M.2 PCIe (NVMe) or SATA SSD Support M.2 2280, 2260 and 2242 | 2x M.2 PCIe (NVMe) or SATA SSD Support M.2 2280, 2260 and 2242 | Dimensions (HxWxD) 185.5x170x230 mm |
| USB | 2x USB 3.2 Gen 1 (1x Front; 1x Rear) | 2x USB 3.2 Gen 1 (1x Front; 1x Rear) | 1x USB 3.2 Gen 1 (Front); 2x USB 3.2 Gen 2 (Rear) | Weight 2.7kg/5.95lbs |
| LAN | 2x 2.5 Gigabit (Wake On WAN), 2x 10 Gigabit | 2x 2.5 Gigabit (Wake On WAN), 2x 10 Gigabit | 3x 2.5-Gigabit, 1x 10-Gigabit | Disk Tray Lock Yes |
| Expansion | — | — | — | Front Panel LED Power, Status, Link, Alert, HDD |
| Dimensions(HxWxD) | 215.5x293x230 mm | 215.5x293x230 mm | 215.5x293x230 mm | Power Supply 90W AC Adapter |
| Weight | 6.2kg/13.67lb | 6.4kg/14.1lb | 7.1 kg/15.62 lb | Volume Type Single, JBOD, RAID 0/1/5/6/10, RAID 1/5 + Hot Spare |
| Power | 250W | 250W | 350W | |
| Operation | 66.9W | 76.8W | 78.7W | |
| Disk Hibernation | 37.2W | 41.1W | 40.1W | |
| Sleep Mode (S3) | No Sleep Mode | No Sleep Mode | Yes | |
| Volume Type | Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Hot Spare | Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Hot Spare | Single, JBOD, RAID 0/1/5/6/10, RAID 0/1/5/6/10 + Hot Spare | |
| Display Out | — | — | — | |
| Infrared Receiver | — | — | — | |
| Service LED | — | — | — | |
| Disk Tray Lock | Yes | Yes | Yes | |
| LCD Panel | Yes | Yes | Yes | |

*Must be Used in Combination with ADM 3.0 or above

ASUSTOR Inc.

3F, No. 136, Daye Rd., Beitou Dist., Taipei City 112, Taiwan
Tel: +886 2 7737 0888

Designs and specifications are subject to change without notice.
© ASUSTOR Inc. ASUSTOR and all other ASUSTOR product names are trademarks or registered trademarks of ASUSTOR Inc. All other product and company names mentioned herein are the trademarks of their respective owners.



www.asustor.com

Dealer Seal

1553-COENG021-210

Small & Medium Business

| |  Lockerstor 4RS/4RD AS6504RS/AS6504RD |  Lockerstor 12RD AS6512RD |  Lockerstor 12R Pro AS7112RDX, 2U |  Lockerstor 16R Pro AS7116RDX, 3U |
|--------------------------|--|--|---|--|
| Processor | Intel ATOM C3538 2.1GHz Quad-Core | Intel ATOM C3538 2.1GHz Quad-Core | Intel 9 th generation Quad-Core Xeon 4.6GHz Turbo | Intel 9 th generation Quad-Core Xeon 4.6GHz Turbo |
| Memory | 8GB SO-DIMM DDR4 (Expandable. max. 128GB, 32GB x4) | 8GB SO-DIMM DDR4 (Expandable. max. 128GB, 32GB x4) | 8GB ECC UDIMM DDR4-2666 (Expandable. max. 128GB, 32GB x4) | 8GB ECC UDIMM DDR4-2666 (Expandable. max. 128GB, 32GB x4) |
| Drive Bays | 4x 2½"/3½" SATA III | 12x 2½"/3½" SATA III | 12x 2½"/3½" SATA III | 16x 2½"/3½" SATA III |
| M.2 | — | — | 2x M.2 PCIe (NVMe) or SATA SSD Support M.2 22110, 2280, 2260 and 2242 | 2x M.2 PCIe (NVMe) or SATA SSD Support M.2 22110, 2280, 2260 and 2242 |
| USB | 4x USB 3.2 Gen 1 | 4x USB 3.2 Gen 1 | 4x USB 3.2 Gen 2 (Type A), 2x USB 3.2 Gen 2 (Type C) | 4x USB 3.2 Gen 2 (Type A), 2x USB 3.2 Gen 2 (Type C) |
| LAN | 2x 2.5 Gigabit (Wake On WAN) 2x 1 Gigabit | 2x 2.5 Gigabit (Wake On WAN) 2x 1 Gigabit | 4x Gigabit | 4x Gigabit |
| Expansion | 1x for optional expansion 10 GbE card | 1x for optional expansion 10 GbE card | 3x for optional expansion 10,25,40,50GbE card and SAS card | 3x for optional expansion 10,25,40,50GbE card and SAS card |
| Dimensions(HxWxD) | 44x439x515 mm | 88x439x535 mm | 88x439x535 mm | 132x439x535 mm |
| Weight | 4RS: 7.85kg/17.27lb, 4RD: 9.3kg/20.46lb | 11.7kg/25.74lb | 13 kg/28.6 lb | 15.3 kg/39.6 lb |
| Power | 4RS: 250W x1, 4RD: 250W x2 | 350W x2 (80 Plus Gold) | 550W x2 (80 Plus Platinum) | 550W x2 (80 Plus Platinum) |
| Operation | 4RS: 47.7W, 4RD: 65W | 115W | 92.4W | 121.7W |
| Disk Hibernation | 4RS: 28.4W, 4RD: 42.4W | 67W | 45.5W | 51.5W |
| Sleep Mode (S3) | No Sleep Mode | No Sleep Mode | 7.55W | 7.55W |
| Volume Type | Single, JBOD, RAID 0/1/5/6/10, RAID 1/5 + Hot Spare | Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Hot Spare | Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Hot Spare | Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Hot Spare |
| Display Out | — | — | — | — |
| Infrared Receiver | — | — | — | — |
| Service LED | Yes | Yes | Yes | Yes |
| Disk Tray Lock | Yes | Yes | Yes | Yes |
| LCD Panel | — | — | — | — |

Software & Features

Operating System

- ADM 4.0 Onwards
- Supports Online Firmware Updates
- Built-in App Central for Various Apps

Supported OS

- Windows XP, Vista, 7, 8, 10, Server 2003, Server 2008, Server 2012, Server 2016
- macOS 10 Onwards
- UNIX, Linux, BSD

Access Control

- Supports 2-Step Verification
- Supports Batch Creation and Importation of ADM Accounts
- Supported Importation File Format: txt, csv
- Maximum Number of Users: 4096/16384 (AS71 series)
- Maximum Number of Groups: 512
- Maximum Number of Shared Folders: 512
- Maximum Number of Concurrent Connections: 512/2048 (AS71 series)
- Supports Windows Active Directory/LDAP

File Explorer

- Web-based File Management
- ISO File Mounting · Share Links
- Data Access via External Optical Drive
- Supports video playback

ACL

- Provides both Windows ACL and Linux ACL permission configuration methods
- Can enable Windows ACL for specific shared folders
- Comprehensive support for Windows' 13 types of advanced permission settings
- Can view Windows ACL permission settings from within ADM
- Supports local users and groups
- Exclusive permission reset function allows users to quickly restore default permissions

SSD Cache

- SSD-like performance with traditional hard drives
- supports read-only access and read-write cache mode
- Supported Models: AS52/53/63/64/Lockerstor/Lockerstor Pro series

M.2 Storage

- Supported Models: Lockerstor 2/4/8/10/10 Pro/12R Pro/ 16R Pro

Customized Sign In Page

- Light and dark modes
- Customizable Title, Image and Background
- Move around the login details dialogue box
- Image Import Function
- System Announcements
- App Shortcuts

Energy Control

- Configurable Disk Hibernation and Sleep Mode Wait Time
- Configurable Time Period for Sleep Mode Activation

Backup Solutions (Two-Way Backup)

- Rsync (Remote Sync) Backup
- Cloud Backup · FTP Backup
- External Backup · One Touch Backup
- Internal Backup
- Apple® Time Machine® backup application
- ASUSTOR Backup Plan (Windows)
- EZ Sync

EZ Sync Manager

- Automatically synchronizes files between a PC and NAS
- Can restore previous versions of files
- Supports file sharing
- AiData now supports accessing EZ Sync files

Disk Management

- Scheduled Bad Block Scans
- Scheduled S.M.A.R.T Scans
- Seagate IronWolf Health Management

External Devices

- Supports USB/eSATA External Storage Devices
- USB Wi-Fi Dongle Support
- Bluetooth Dongle/Speaker Support
- USB Printer Support
- USB DAC/IR Receiver/Keyboard/Mouse Support
- USB CD ROM Drive/DVD ROM Drive/BD-ROM

iSCSI

- Maximum Targets: 256
- Maximum Snapshot Versions of a Single LUN: 256
- Maximum LUNs: 256/512 (AS71 series)
- Supports Scheduled LUN Snapshot
- Target Masking
- LUN Mapping
- ISO File Mounting
- Supports MPIO
- Persistent (SCSI-3) Reservations

Supported Browsers

- Firefox · Chrome
- Safari · Microsoft Edge

MyArchive

- Insert Hard Disk & Immediately Access Files
- Transfer or Exchange Terabytes of Data via the Internal Hot-Swap SATA Interface
- Supported MyArchive Bay Number: N-1
- Supported File System Formats: EXT4, NTFS, HFS+, exFAT, Btrfs
- Btrfs Snapshot Supported Models: AS52/53/63/64/Lockerstor/Lockerstor Pro series
- Supports Self-defined Alias Name
- Supports AES 256-bit Encryption for MyArchive Disks (EXT4 and Btrfs only)

File System

- Internal Disk: ext4, Btrfs*
 - External Disk: FAT32, NTFS, ext3, ext4, HFS+, exFAT, Btrfs*
- *Btrfs is only supported on: AS52/53/63/64/Lockerstor/Lockerstor Pro series

DHCP Server

- Supports multiple IP subnet assignments
- Supports Lease Time, DHCP Reservation

Network

- TCP/IP (IPv4 & IPv6)
- Jumbo Frames (MTU)
- VLAN
- EZ-Connect
- Wireless Network
- DDNS and EZ-Router
- Supports Wake-on-LAN (WOL)
- Supports Wake-on-WAN: AS52/53/63/64/Driverstor/Driverstor Pro/Lockerstor series

Network Protocols

- CIFS/SMB, SMB 2.0/3.0, AFP, NFS, FTP (Unicode Supported), TFTP, WebDAV, Rsync, SSH, SFTP, iSCSI, HTTP, HTTPS, Proxy, SNMP, Syslog

Storage Management

- Support Multiple Volumes with Spare Disks
- Volume Type: Single disk, JBOD, RAID 0, RAID 1, RAID 5, RAID 6, RAID 10
- Support for Online RAID Level Migration
- Support for Online RAID Capacity Expansion

Supported Languages

- Deutsch, English, Français, Italiano, Nederlands, Русский, 日本語, 한글, 简体中文, 繁體中文, Ceská, Polski, Svenska, Dansk, Norsk, Suomi, Português, Türkçe, Español, Magyar

System Administration

- Support scheduled upgrade ADM & AppLog Type: System Log, Connection Log, File Access Log
- Real-time Online User Monitor
- Real-time System Monitor
- User Quota
- Virtual Drive (ISO Mounting, Maximum 16)
- UPS Support

Network Recycle Bin

- Share folder-based
- Maintains original directory structure and file permission
- On-click restore
- Supports scheduled emptying
- Filtering rules (1.File size 2.File extension)
- Deletion Settings (1.File size 2.File date)

Security

- AES 256-Bit Folder Encryption
- Built-in Hardware Encryption Engine: AS52/53/63/64/Drivestor/Drivestor Pro/Lockerstor/Lockerstor Pro series
- Firewall: Prevent Unauthorized Access
- Network Defender: Prevent Network Attacks
- Encrypted Connections: HTTPS, FTP over SSL/TLS, SSH, SFTP, Rsync over SSH
- Supports Let's Encrypt
- Supports Intermediate Certificate
- Alert Notifications: E-mail, SMS, Pushbullet, Pushover, AiMaster
- RAID Scrubbing: detects the integrity and consistency of RAID 5 and RAID 6 drive data

Snapshot Center

- Btrfs snapshots
- Max: 256 snapshots
- Integrated with existing iSCSI LUNs snapshots
- Applicable series: AS52/53/63/64/Lockerstor/Lockerstor Pro series
Snapshot Center will not display Volume snapshots information in other models.

Web Center

- Install Apache or Nginx or almost any other web server implementation

Featured Apps

Antivirus

- Scheduled Scans
- Automatic Virus Definition Updates
- Quarantine Infected Files

ASUSTOR Portal (HDMI Local Output)¹

- Simultaneously view 4 channels of high resolution real-time video feeds and playback recordings
- Power Control Settings: Power on, Sleep, Restart and Wake via Remote
- Customizable ASUSTOR Portal Desktop Wallpaper
- Add Shortcuts to Favorite Websites
- Increased TV Compatibility via Overscan and Resolution Settings
- Max resolution: 1080p (HD)/2160p (4K)²
- ADM integrated for local system management
- URL-Pack connects popular video streaming websites, URL-Pack-Social provides links to a variety of social media platforms

Download Center

- Supports BT (Torrent & Magnet Link), HTTP and FTP Downloads
- Torrent Search
- Choose Files Before a BT Task Starts
- Customizable Download Schedule
- Bandwidth Control
- RSS Subscription and Automatic Downloading (Broadcatching)
- ASUSTOR Download Assistant for Windows & Mac
- AiDownload for Android
- Smart Downloads

FTP Explorer

- Directory Structure View with Drag & Drop Transfers
- Task Monitor
- Stopping of Transmission Task & Resumption of Connection
- Encrypted Connections: Explicit over TLS, Implicit over TLS
- FTP Site Manager
- Bandwidth Control

DataSync for CloudDrive/DataSync Center

- Support Google Drive, HiDrive, Dropbox, Microsoft OneDrive, Yandex
- Each ADM account is able to individually log into a Cloud Storage account
- Supported backup methods:
 - Sync
 - Directly upload files to Cloud from NAS
 - Directly download files from Cloud to NAS

OwnTone

- For iTunes on Mac & Windows
- Supports AirPlay/Chromecast
- Supports iOS Remote Pairing

Plex Media Server

- Plex is currently a well-received multimedia center
- Plex Supports a Wide Range of Devices

VirtualBox

- Virtual Machines are Able to run the Following Operating Systems: Windows, Linux, Solaris, macOS
- Virtual Machine Import Format: OVF
- Virtual Machine Export Format: OVF 0.9, OVF 1.0, OVF 2.0
- Virtual Machine Snapshots
- Virtual Machine HDMI Audio Output
- Physical NAS Network Port can be Designated for use by Specific Virtual Machine
- Recommends 2GB RAM or more to run Windows/Linux, and 4GB RAM or more to run other OS

RADIUS Server

- Centralized management of wireless network certification
- Using WPA-Enterprise or WPA2-Enterprise encryption
- Must be combined with a wireless router that supports RADIUS authentication

Mail Server

- Each ADM Account can Become an Independent Email Account
- Email Activity Monitor (Over 1 Week, 1/3/6 Months)
- Provides SMTP, IMAP and POP3 Mail Protocols
- Supports SMTP Relay and Verification
- SMTP-SSL Secure Connections
- Spam Filter and Black List Settings
- Antivirus Scanning for Emails
- Email Alias Creation and Mapping
- Monitoring of Mail Queue
- Mail Service Activity Log
- Exclusive Email Backup Mechanism
- Auto-Forwarding and Auto-Response Protocols

LooksGood

- Built-in three main video library categories and smart video sorting management
- Efficient Global Search function allows for searches by keywords followed by the execution of more detailed searches
- Attractive poster wall and thumbnail display
- Automatic production of video poster thumbnails
- Centralized management and ability to configure order of favorites and playlist history
- System administrator can configure video library and editing permissions according to user
- Can configure access permissions to share with friends and family
- Multimedia conversion function
- Self-defined smart folder for video conversions
- Easy streaming with Chromecast and DLNA

Photo Gallery 3

- Timeline view
- Smart Album
- Supports shared folder structure with "Folders" mode
- Now able to select any shared folder on a NAS for storing photos
- Easily adjustable preview sizes and modes. Includes adjusting by day, month, and year
- Comprehensive search function: Can use keywords to search within photos, albums, and folders. It can also specify search criteria such as file type and time
- Selecting multiple photos to rotate, tag, add to favorites, and share
- Slideshow viewing mode with playing favorite songs
- Supports a wide range of image formats: RAW, PNG, JPEG, TIFF, GIF, HEIC
- Support mobile shot video playback
- View EXIF information and edit photo descriptions

SoundsGood

- Import Personal/Public Music Collection
- Personal/Public Music Collection Permission Control
- Playlist Editor
- ID3 Tag Editor
- Local Speaker Support: HDMI, USB
- Local Network Audio Output Support: AirPlay Devices

Takeasy

- Download from YouTube, Twitch, Vimeo, YouKu and more
- Selectable the Video Type and Quality
- Automatic Downloads with Subscriptions
- Preview Downloads in Progress
- Online Playback

Cloud Backup Center

- Support Amazon S3, Backblaze B2, Microsoft Azure Blob Storage, Alibaba Cloud, Baidu Cloud, IBM Cloud and Rackspace Cloud Files
- Immediate or scheduled backup
- Perform multiple backup tasks and back up multiple accounts

Linux Center

- Integrate NAS operating system with Linux
- Flexible use of the Linux App
- Easy installation with just one touch
- HDMI output on command

Surveillance Center

- On-screen camera controls including camera PTZ, manual recordings, take snapshots, configure camera settings and open Maps
- Up to 4 channels of synchronous and non-synchronous playback with audio
- Intelligent video analytics including motion detection and foreign object detection
- Supported Browsers: Firefox, Chrome, Microsoft Edge
- Event notification supports SMS, E-mail, and mobile push notification
- Automated event action rules
- Role-based access control
- AiSecure mobile app for iOS and Android
- ONVIF Profile S, T supported
- Two different camera license packages are offered: single channel and 4 channels
- Please check ASUSTOR website for maximum IP cameras.
- CMS Lite support centralize management for up to 128 IP Camera
- Minimum Computer System Requirements:
 - CPU: Intel i5/i7, AMD Phenom II or above
 - RAM: DDR3 4GB or Above
 - Supported Operating Systems:
 - Windows 7 and onwards
 - Recommended Monitor Resolution: 1280x800 Pixels
 - Network Interface: Gigabit x1
 - Dedicated Graphics Card is Recommended

UPnP Media Server

- Offers 2 Different Server Choices: UPnP v2, MiniDLNA
- Supports PS3/Xbox and Other UPnP Compatible Players
 - * The supported formats may differ depending on the UPnP client in use.

VPN Client

- Supports PPTP & OpenVPN settings
- View Current Connections & Ability to Disconnect
- Suspicious Connections
- Comprehensive Connection Log

VPN Server

- Supported VPN settings: PPTP, OpenVPN & IPsec/L2TP Transmission Package Monitor
- PPTP Authentication: PAP, CHAP, MS CHAP, MS CHAP2
- PPTP Encryption: No MPPE, MPPE (40, 128 bit), Maximum MPPE (128 bit)
- OpenVPN Port Control
- OpenVPN Link Compression
- Supports OpenVPN Configuration Files Importation

ASUSTOR Live

- Multistreaming (Including, but not limited to YouTube, Twitch, Facebook, Instagram, Restream or RTMP compatible platforms.)
- Streaming video save and use

Portainer and Docker

- Easy Docker Deployments

Note:

1. ASUSTOR recommends that ASUSTOR Portal be used with a TV with a resolution of 720p or higher or a monitor supporting audio output.
2. Currently, AS52/53/63/64/Lockerstor 2&4 Series Devices are able to provide 4K Output at 60Hz.