

asustor

More Than Just Storage

Discover the Extraordinary with ASUSTOR



Performance King



Boundless Functionality



Intuitive UI



Incredible Value



Warranty Service



ASUSTOR Data Master

Features of ADM 5.0

Customizable Toolbar

ADM now comes with a brand new toolbar for ADM 5.0. The toolbar can now be placed at either the top or the bottom of the page. In addition, the toolbar can be set to automatically hide when not in use on desktop platforms.

All-New ADM Defender

The all-new ADM Defender provides preset and customizable firewall profiles. Intelligent security protection can proactively prevent suspicious IP addresses from connecting to your NAS. ADM can also monitor network transmission packets to intercept suspicious network activities. The new design makes it easier to enable the firewall and additional security protections. ADM Defender proactively prevents suspicious connections, which can help further reduce the risks of malware and attacks to further improve data security.

SSH Keys Make SSH Logins More Secure

Logging into an ASUSTOR NAS using SSH means you can exercise full control over your NAS and operate more advanced functions. Enabling SSH keys can improve the security of using SSH while also making it more convenient. SSH keys replace passwords and are much more secure than passwords. Generate different keys for different administrator accounts and save the private keys in an SSH client while disable password authentication, greatly improving the security of SSH connections.

Upgraded Samba - Better Performance

ADM 5.0 brings a new version of Samba. With the new version of Samba, SMB Multichannel is no longer experimental and brings new performance enhancements, additional security and is much more stable than ever before. Combine two, three or four Ethernet ports on your ASUSTOR NAS with your computer to receive up to double, triple, or even quadruple performance respectively for maximum speed.

Fast – Secure – Stable

ADM 5.0 has been upgraded to Linux kernel 6.6 LTS. Kernel 6.6 LTS introduces numerous security patches that help make ASUSTOR NAS devices safer than ever. Kernel 6.6 also continues to enhance ADM performance and stability, while also adds compatibility with even more hardware for maximum flexibility.

Edit Plain Text Files

Install the new Text Editor from App Central to add or edit various plain text files on ADM 5.0. There is no need to download or create text files on a computer or phone for editing when your NAS is able to do it.

Surveillance Center

Instant Notifications

Surveillance Center supports push notifications, emails and SMS messages to individual cameras and events.

Centralized Surveillance Software - CMS Lite

CMS Lite allows surveillance professionals to have more flexibility and convenience when monitoring and playing back video. Manage up to 256 IP cameras and ASUSTOR NVRs in up to 32 different locations.

Multi-Stream

Surveillance Center supports 3 independent video streaming modes, allowing administrators to configure default resolutions for recordings and viewing feeds remotely. Select resolutions based on network bandwidth and the number of channels that they are viewing, optimizing video streaming under different network bandwidth limitations.

Smart Passive & Active Recording Modes

Surveillance Center provides a variety of passive and active recording modes, regardless of whether you require scheduled recording for a specific time period or simply record once an event has occurred.



Automated Event Action Rules

Automated event action rules allow administrators to customize alarm handling rules. When an event occurs, your NAS can select different measures to handle a situation based on the type of event or the time the event occurred.



Business

Comprehensive Backup Solutions: Centrally Backup and Manage Data from Different NAS Models and Brands

- Internal backups + MyArchive = Offsite data protection + Unlimited storage capacity expansion
- Use FTP, SMB, Rsync for two-way backup and secure data transfers
- Use DataSync Center for two-way backup to another ASUSTOR NAS through EZ Sync
- Backup and restore phone data with AiData and AiFoto 3
- Back up to cloud services easily with Cloud Backup Center or DataSync Center. Supports Amazon S3, Azure, Google Drive, Google Cloud Storage, HiDrive, Dropbox, OneDrive, hicloud and more
- USB One Touch backups or back up to the ASUSTOR Xpanstor 4 (AS5004U)

Virtualization Ready

Complete iSCSI/IP-SAN and NFS support. VMware, Citrix and Hyper-V ready.

Ransomware recovery - Snapshot Center

ASUSTOR NAS devices support snapshots on Btrfs volumes and iSCSI volumes, ensuring that if ransomware attacks, changes are reversible.

Evolved Network Defender

- Block brute-force attacks with the automatic blacklist
- Trust List can prevent trusted IP addresses from being automatically blocked in the event of too many inadvertent login failures
- The blacklist and whitelist can be defined by specific IPs, IP ranges, and geolocation

Seamless integration with AD, ACL and LDAP

LDAP and Windows AD support combined with ACL allows IT professionals to use the permissions and security settings in Windows to quickly configure shared folder access rights for users and groups on an ASUSTOR NAS. These settings can be applied to Samba, File Explorer, AFP, NFS, or WebDAV allowing businesses to maintain flexibility and security with regards to data access.

EZily connect to your NAS with EZ-Connect and ezconnect.to

Easily connect remotely to your NAS even in network environments with multiple routers from within the network. ASUSTOR's EZ-Connect supports a variety of features, including, but not limited to Internet passthrough and remote shared folder mounting on Windows Explorer. EZ-Connect.to uses a web browser to connect to a NAS remotely and access data.

Lifestyle Applications


*Limited to some models



The Dynamic ASUSTOR Portal*



Ultimate Audio Enjoyment with SoundsGood



ASUSTOR Live



Photo Gallery 3 Brings Smart Photo Management



Your Dedicated Cinema: LooksGood



WOW (Wake on WAN), Always on Standby*

Mobile Apps

AiMaster

Initialize a NAS easily without a PC by using AiMaster on a phone to set up and manage your NAS. No matter if it is adding new users, creating shared folders, remote wake-up, installing exciting new NAS Apps, upgrading your firmware or checking the real-time status of your system.

AiDownload

Use your Android device to search for torrents and easily add downloads to Download Center on your NAS. Easily monitor current downloads, establish new downloads and RSS feeds and instantly receive push notifications for completed downloads on your Android phone or tablet.

AiRemote

Control ASUSTOR Portal without a keyboard and mouse. From navigating the media player menus to controlling video playback and adjusting volume, AiRemote makes it easy. Additionally, AiRemote provides touchpad and keyboard modes when using the included browser.

AiMusic

AiMusic makes streaming music from your NAS to your phone or tablet easy. Effortlessly select songs from different genres in an organized music library or even download entire playlists to your mobile device for offline listening. Enabling random playback allows you to create a random playlist at any time.

AiData

AiData brings access to your NAS's files to your smartphone or tablet. AiData helps you browse and manage files on your NAS directly from your phone or tablet. AiData also supports file sharing, making it easy to share files right from your smartphone and tablet, bringing your data to your fingertips.

AiFoto 3

The all new AiFoto 3 has been revamped and brings a variety of new features to make photo organization easier than ever. New features for AiFoto3 include, timelines, smart albums, deduplication and free up space. Support for HEIC images and custom share links make for an even better photo viewing and sharing experience.

AiVideos

AiVideos supports real-time transcoding, enabling a high resolution video streaming experience by selecting the video of your choice from the app. AiVideos also supports Chromecast and Apple TV, allowing you to stream your videos to the big screen and share them with friends and family.

AiSecure

AiSecure allows you to effortlessly keep an eye on your most valued assets. In addition to monitoring live surveillance feeds, push notifications can be sent immediately to your mobile device in the event of any disruptions, allowing you to keep watch over your personal property.

Hardware Specifications

Personal to Home

	 DRIVESTOR 2 Lite AS1102TL	 DRIVESTOR 4 AS1104T	 DRIVESTOR 2 Pro Gen2 AS3302T v2	 DRIVESTOR 4 Pro Gen2 AS3304T v2
Processor	Realtek RTD1619B 1.7 GHz Quad-Core Processor	Realtek RTD1296 1.4 GHz Quad-Core Processor	Realtek RTD1619B 1.7 GHz Quad-Core Processor	Realtek RTD1619B 1.7 GHz Quad-Core Processor
Memory	1GB DDR4 (non-upgradeable)	1GB DDR4 (non-upgradeable)	2GB DDR4 (non-upgradeable)	2GB DDR4 (non-upgradeable)
Drive Bays	2x 3½" SATA III	4x 3½" SATA III	2x 2½"/3½" SATA III	4x 2½"/3½" SATA III
M.2 Slots	-	-	-	-
USB	1 x USB 3.2 Gen1x1; 1 x USB 2.0	2x USB 3.2 Gen 1	3x USB 3.2 Gen 1	3x USB 3.2 Gen 1
LAN	1 x Gigabit Ethernet	1x 2.5-Gigabit (Wake On WAN)	1x 2.5-Gigabit (Wake On WAN)	1x 2.5-Gigabit (Wake On WAN)
Expansion	-	-	-	-
Dimensions(HxWxD)	165x102x218 mm	165x164x218 mm	170x114x230 mm	170x174x230 mm
Weight	1.14kg / 2.5lb	1.57kg / 3.45lb	1.6kg / 3.53lb	2.2kg / 4.85lb
Power	65W AC Adapter	90W AC Adapter	65W AC Adapter	90W AC Adapter
Operation	11.7W	22.8W	13.1W	25.1W
Disk Hibernation	3.1W	9.41W	4.5W	8.4W
Sleep Mode (S3)	-	-	-	-
Volume Type	Single, JBOD, RAID 0/1	Single, JBOD, RAID 0/1/5/6/10	Single, JBOD, RAID 0/1	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5 + Spare Drive
Display Out	-	-	-	-
Service LED	-	-	-	-
Disk Tray Lock	-	-	-	-
LCD Panel	-	-	-	-
Audio Output	-	-	-	-


Hardware Specifications

Home to Power User		Power User to Business		
	 NIMBUSTOR 2 Gen 2 AS5402T	 NIMBUSTOR 4 Gen 2 AS5404T	 FLASHSTOR 6 FS6706T	 FLASHSTOR 12 Pro FS6712X
Processor	Intel Celeron N5105 Quad-Core, 2.0 GHz up to 2.9 GHz		Intel Celeron N5105 Quad-Core, 2.0 GHz up to 2.9 GHz	
Memory	4GB DDR4-2933 SO-DIMM (Expandable. max. 16GB, 8GB x2)		4GB DDR4-2933 SO-DIMM (Expandable. max. 16GB, 8GB x2)	
Drive Bays	2x 2½"/3½" SATA III		-	
M.2 Slots	4x M.2 PCIe (NVMe) Support M.2 2280		6x M.2 PCIe (NVMe) Support M.2 2280 Supports PCIe 3.0	
USB	3x USB 3.2 Gen2 (1x Front ; 2x Rear)		2x USB 3.2 Gen2 (1x Front ; 1x Rear) 2x USB 2.0	
LAN	2x 2.5-Gigabit (Wake On WAN)		2x 2.5-Gigabit (Wake On WAN)	
Expansion	-		-	
Dimensions(HxWxD)	170x114x230 mm		48.3x308.26x193 mm	
Weight	1.71kg / 3.77lb		1.35 kg / 2.98 lb	
Power	65W AC Adapter		65W AC Adapter	
Operation	22.9W		18.2 W	
Disk Hibernation	12.7W		-	
Sleep Mode (S3)	0.71W		0.83 W	
Volume Type	Single, JBOD, RAID 0/1		Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Spare Drive	
Display Out	1x HDMI™		1x HDMI™	
Service LED	-		-	
Disk Tray Lock	-		-	
LCD Panel	-		-	
Audio Output	-		1x S/PDIF	

Power User to Business			
			
	LOCKERSTOR 2 Gen2 AS6702T	LOCKERSTOR 4 Gen2 AS6704T	LOCKERSTOR 6 Gen2 AS6706T
Processor	Intel Celeron N5105 Quad-Core, 2.0GHz up to 2.9GHz		Intel Celeron N5105 Quad-Core, 2.0GHz up to 2.9GHz
Memory	4GB DDR4-2933 SO-DIMM (Expandable. max. 16GB, 8GB x2)		8GB DDR4-2933 SO-DIMM (Expandable. max. 16GB, 8GB x2)
Drive Bays	2x 2½"/3½" SATA III		6x 2½"/3½" SATA III
M.2 Slots	4x M.2 PCIe (NVMe) Support M.2 2280		4x M.2 PCIe (NVMe) Support M.2 2280
USB	2x USB 3.2 Gen2 (1x Front ; 1x Rear)		2x USB 3.2 Gen2 (1x Front ; 1x Rear)
LAN	2x 2.5-Gigabit (Wake On WAN)		2x 2.5-Gigabit (Wake On WAN)
Expansion	-		1x for optional expansion 10 GbE card*
Dimensions(HxWxD)	163.5x108x230 mm		185.5x233x230 mm
Weight	2 kg / 4.41 lb		4.4 kg / 9.7 lb
Power	65W AC Adapter		250W
Operation	21W		48.5W
Disk Hibernation	13.5W		27.7W
Sleep Mode (S3)	0.79W		0.81W
Volume Type	Single, JBOD, RAID 0/1		Single, JBOD, RAID 0/1/5/6/10, RAID 1/5 + Spare Drive
Display Out	1x HDMI™		1x HDMI™
Infrared Receiver	Yes		Yes
Service LED	-		-
Disk Tray Lock	Yes		Yes
LCD Panel	-		Yes
Audio Output	-		-

*Installation of 10GbE NIC requires removal of M.2 daughterboard

Power User to Business

	 FLASHSTOR 6 Gen2 FS6806X	 FLASHSTOR 12 Pro Gen2 FS6812X
Processor	AMD Ryzen V3C14 Quad-Core, 2.3 GHz up to 3.8 GHz	AMD Ryzen V3C14 Quad-Core, 2.3 GHz up to 3.8 GHz
Memory	8GB DDR5-4800 SO-DIMM (Expandable. max. 64GB, ECC supported)	16GB ECC DDR5-4800 SO-DIMM (Expandable. max. 64GB)
Drive Bays	-	-
M.2 Slots	6x M.2 PCIe (NVMe) Support M.2 2280 Supports PCIe 4.0	12x M.2 PCIe (NVMe) Support M.2 2280 Supports PCIe 4.0 and 3.0
USB	3x USB 3.2 Gen 2 (2x Front; 1x Rear) 2 x USB 4.0 Type-C (2x Rear)	3x USB 3.2 Gen 2 (2x Front; 1x Rear) 2 x USB 4.0 Type-C (2x Rear)
LAN	1x 10-Gigabit	2x 10-Gigabit
Expansion	-	-
Dimensions(HxWxD)	48.3x308.26x193 mm	48.3x308.26x193 mm
Weight	1.4 kg / 3.08 lb	1.45 kg / 3.19 lb
Power	90W AC Adapter	120W AC Adapter
Operation	17.9W	33.2W
Disk Hibernation	-	-
Sleep Mode (S3)	1.2W	2.8W
Volume Type	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Spare Drive	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Spare Drive
Display Out	-	-
Service LED	-	-
Disk Tray Lock	-	-
LCD Panel	-	-
Audio Output	-	-

Power User to Business

	 LOCKERSTOR 4 Gen3 AS6804T	 LOCKERSTOR 6 Gen3 AS6806T	 LOCKERSTOR 8 Gen3 AS6808T	 LOCKERSTOR 10 Gen3 AS6810T
Processor	AMD Ryzen V3C14 Quad-Core, 2.3 GHz up to 3.8 GHz	AMD Ryzen V3C14 Quad-Core, 2.3 GHz up to 3.8 GHz	AMD Ryzen V3C14 Quad-Core, 2.3 GHz up to 3.8 GHz	AMD Ryzen V3C14 Quad-Core, 2.3 GHz up to 3.8 GHz
Memory	16GB ECC DDR5-4800 SO-DIMM (Expandable. max. 64GB, 32GB x2)	16GB ECC DDR5-4800 SO-DIMM (Expandable. max. 64GB, 32GB x2)	16GB ECC DDR5-4800 SO-DIMM (Expandable. max. 64GB, 32GB x2)	16GB ECC DDR5-4800 SO-DIMM (Expandable. max. 64GB, 32GB x2)
Drive Bays	4x 2½"/3½" SATA III	6x 2½"/3½" SATA III	8x 2½"/3½" SATA III	10x 2½"/3½" SATA III
M.2 Slots	4x M.2 slots for NVMe SSDs Supports M.2 2280 SSDs Supports PCIe 4.0	4x M.2 slots for NVMe SSDs Supports M.2 2280 SSDs Supports PCIe 4.0	4x M.2 slots for NVMe SSDs Supports M.2 2280 SSDs Supports PCIe 4.0	4x M.2 slots for NVMe SSDs Supports M.2 2280 SSDs Supports PCIe 4.0
USB	3x USB 3.2 Gen 2 (2x Front; 1x Rear); 2 x USB 4.0 Type-C (2x Rear)	3x USB 3.2 Gen 2 (2x Front; 1x Rear); 2 x USB 4.0 Type-C (2x Rear)	3x USB 3.2 Gen 2 (2x Front; 1x Rear); 2 x USB 4.0 Type-C (2x Rear)	3x USB 3.2 Gen 2 (2x Front; 1x Rear); 2 x USB 4.0 Type-C (2x Rear)
LAN	2x 5-Gigabit (Wake On LAN/WAN); 2x 10-Gigabit	2x 5-Gigabit (Wake On LAN/WAN); 2x 10-Gigabit	2x 2.5 Gigabit (Wake On WAN); 2x 10 Gigabit	2x 2.5 Gigabit (Wake On WAN); 2x 10 Gigabit
Expansion	1x for optional expansion 10 GbE card (*) Installation of 10GbE NIC requires removal of M.2 daughterboard.	1x for optional expansion 10 GbE card (*) Installation of 10GbE NIC requires removal of M.2 daughterboard.	1x for optional expansion 10 GbE card (*) Installation of 10GbE NIC requires removal of M.2 daughterboard.	1x for optional expansion 10 GbE card (*) Installation of 10GbE NIC requires removal of M.2 daughterboard.
Dimensions(HxWxD)	185.5x170x230 mm	185.5x233x230 mm	215.5x293x230 mm	215.5x293x230 mm
Weight	3.2 kg / 7.06 lb	4.6 kg / 10.14lb	6.45 kg / 14.22 lb	6.55 kg / 14.44 lb
Power	90W AC Adapter	250W	250W	250W
Operation	34W	45W	58.5W	68W
Disk Hibernation	18W	20W	25W	26W
Sleep Mode (S3)	2.3W	2.3W	2.4W	2.4W
Volume Type	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5 + Spare Drive-	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Spare Drive	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Spare Drive	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Spare Drive
Display Out	-	-	-	-
Service LED	-	-	-	-
Disk Tray Lock	Yes	Yes	Yes	Yes
LCD Panel	Yes	Yes	Yes	Yes
Audio Output	-	-	-	-

*Installation of 10GbE NIC requires removal of M.2 daughterboard / **TBP (To be provided)



www.asustor.com




ASUSTOR Inc.





3F, No.136, Daye Rd., Beitou Dist., Taipei City 112, Taiwan
Tel: +886 2 7737 0888

Designs and specifications are subject to change without notice.
© ASUSTOR Inc. ASUSTOR and all other ASUSTOR product names are trademarks or registered trademarks of ASUSTOR Inc. All other product and company names mentioned herein are the trademarks of their respective owners.

Dealer Seal

1553-C0ENG011-240

Power User to Business		Expansion Units			
<div></div> <div>LOCKERSTOR 10 Pro AS7110T</div>		<div></div> <div>AS5004U</div>		<div><div>New</div></div> <div>XPANSTOR 12R AX7012R</div>	
Processor	Intel 9 th generation Quad-Core Xeon 4.6GHz Turbo	Flash Memory	32MB	Flash Memory	2MB SRAM
Memory	8GB ECC DDR4-2666 SO-DIMM (Expandable,max. 64GB,32GB x2)				
Drive Bays	10x 2½"/3½" SATA III	Expansion	USB 3.2 Gen 2 Type C	Expansion Port	SAS IN-port : 2 SAS Out-port: 2
M.2 Slots	2x M.2 PCIe (NVMe) or SATA SSD Support M.2 2280, 2260 and 2242				
USB	1x USB 3.2 Gen 1 (Front); 2x USB 3.2 Gen 2 (Rear)	HDD	4 x SATA3 6Gb/s; 3.5"/2.5" HDD/SSD	Compatible Drive Type	3.5" SAS 2 HDD; 3.5" SAS 3 HDD; 3.5" SATA 3 HDD
LAN	3x 2.5-Gigabit, 1x 10-Gigabit				
Expansion	-	Maximum Internal Raw Capacity	96 TB (24 TB HDD x4, Capacity may vary by RAID types)	Drive Bays	12
Dimensions(HxWxD)	215.5x293x230 mm				
Weight	7.1 kg / 15.62 lb	Supports Hot Swappable Drives	Yes	Supports Hot Swappable Drives	Yes
Power	350W				
Operation	78.7W				
Disk Hibernation	40.1W				
Sleep Mode (S3)	5.8W	System Fan	120mm x1	System Fan	3x 80x38mm hot-swap cooling fans
Volume Type	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Spare Drive				
Display Out	-	Power Supply Unit/Adapter	90W x1	Power Supply Unit / Adapter	650W x2
Service LED	-				
Disk Tray Lock	Yes	Input Power Voltage	100V to 240V AC	Input Power Voltage	100V to 240V AC
LCD Panel	Yes				
Audio Output	-	Certification	FCC, CE, VCCI, BSMI, C-TICK	Certification	FCC, CE, UKCA, VCCI, BSMI, C-Tick

Small & Medium Business				
	<div></div> <div>LOCKERSTOR 4RS/4RD AS6504RS/RD</div>	<div></div> <div>LOCKERSTOR 12RD AS6512RD</div>	<div><div>New</div></div> <div>LOCKERSTOR 12R Pro Gen2 AS7212RDX, 2U</div>	<div><div>New</div></div> <div>LOCKERSTOR 16R Pro Gen2 AS7216RDX, 3U</div>
Processor	Intel ATOM C3538 2.1GHz Quad-Core	Intel ATOM C3538 2.1GHz Quad Core	AMD Ryzen 7 PRO 7745 Octa-Core, 5.3GHz Turbo	AMD Ryzen 7 PRO 7745 Octa-Core, 5.3GHz Turbo
Memory	8GB SO-DIMM DDR4 (Expandable, max. 128GB, 32GB x4)	8GB SO-DIMM DDR4 (Expandable, max. 128GB, 32GB x4)	16GB ECC UDIMM DDR5-4800 (Expandable, max. 192GB, 48GB x4)	16GB ECC UDIMM DDR5-4800 (Expandable, max. 192GB, 48GB x4)
Drive Bays	4x 2½"/3½" SATA III	12x 2½"/3½" SATA III	12x 2½"/3½" SATA III	16x 2½"/3½" SATA III
M.2 Slots	-	-	1x M.2 slots for NVMe SSDs , Supports M.2 2280 SSDs Supports PCIe 5.0	1x M.2 slots for NVMe SSDs , Supports M.2 2280 SSDs Supports PCIe 5.0
USB	4x USB 3.2 Gen 1	4x USB 3.2 Gen 1	4x USB 3.2 Gen 1 (Type A)	4x USB 3.2 Gen 1 (Type A)
LAN	2x 2.5 Gigabit (Wake On WAN) 2x 1 Gigabit	2x 2.5 Gigabit (Wake On WAN) 2x 1 Gigabit	2x 10-Gigabit , 2x Gigabit	2x 10-Gigabit , 2x Gigabit
Expansion	1x for optional expansion 10 GbE card	1x for optional expansion 10 GbE card	2x for optional expansion 10,25,40,50GbE card and SAS card	2x for optional expansion 10,25,40,50GbE card and SAS card
Dimensions(HxWxD)	44x439x515 mm	88x439x535 mm	88x439x576 mm	116x439x576 mm
Weight	4RS: 7.85kg / 17.27lb , 4RD: 9.3kg / 20.46lb	11.7kg / 25.74lb	14 kg / 30.9 lb	15.3 kg / 33.7 lb
Power	4RS: 250W x1 , 4RD:250W x2	350W x 2 (80 Plus Gold)	550W x2(80 Plus Platinum)	550W x2(80 Plus Platinum)
Operation	4RS: 47.7W , 4RD: 65W	115W	102W	187W
Disk Hibernation	4RS: 28.4W , 4RD: 42.4W	67W	99W	128W
Sleep Mode (S3)	-	-	-	-
Volume Type	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5 + Spare Drive	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Spare Drive	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Spare Drive	Single, JBOD, RAID 0/1/5/6/10, RAID 1/5/6/10 + Spare Drive
Display Out	-	-	-	-
Service LED	Yes	Yes	Yes	Yes
Disk Tray Lock	Yes	Yes	Yes	Yes
LCD Panel	-	-	-	-
Audio Output	-	-	-	-

Software & Features

<div>Operating System</div> <ul style="list-style-type: none">· ADM 5.0 Onwards· Supports Online Firmware Updates	<div>Access Control</div> <ul style="list-style-type: none">· Supports 2-Step Verification· Supports Batch Creation and Importation of ADM Accounts· Supported Importation File Format: txt, csv· Maximum Number of Users: 4096/16384 (Lockerstor Pro series)· Maximum Number of Groups: 512· Maximum Number of Shared Folders: 512· Maximum Number of Concurrent Connections: 512/2048 (Lockerstor Pro G1-G2 series)· Supports Windows Active Directory/LDAP	<div>ACL</div> <ul style="list-style-type: none">· Provides both Windows ACL and Linux ACL permission configuration methods· Can enable Windows ACL for specific shared folders· Comprehensive support for Windows' 13 types of advanced permission settings· Can view Windows ACL permission settings from within ADM· Supports local users and groups· Exclusive permission reset function allows users to quickly restore default permissions
------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SSD Cache

- SSD-like performance with traditional hard drives
- supports read-only access and read-write cache mode

Energy Control

- Configurable Disk Hibernation and Sleep Mode Wait Time
- Configurable Time Period for Sleep Mode Activation

Backup Solutions (Two-Way Backup)

- Rsync (Remote Sync) Backup · SMB Backup
- Cloud Backup · FTP Backup
- External Backup · One Touch Backup
- Internal Backup · EZ Sync
- Apple®Time Machine® backup application
- ASUSTOR Backup Plan (Windows)

Disk Management

- Scheduled Bad Block Scans
- Scheduled S.M.A.R.T Scans
- Seagate IronWolf Health Management

External Devices

- Supports USB/eSATA External Storage Devices
- USB Wi-Fi Dongle Support
- Bluetooth Dongle/Speaker Support
- USB Printer Support
- USB DAC/IR Receiver/Keyboard/Mouse Support
- USB CD ROM Drive/DVD ROM Drive/BD-ROM

iSCSI

- Maximum Targets: 256
- Maximum Snapshot Versions of a Single LUN: 256
- Maximum LUNs: 256/512 (Lockerstor Pro series)
- Supports Scheduled LUN Snapshot
- Target Masking · LUN Mapping
- ISO File Mounting · Supports MPIO
- Persistent (SCSI-3) Reservations

MyArchive

- Insert Hard Disk & Immediately Access Files
- Transfer or Exchange Terabytes of Data via the Internal Hot-Swap SATA Interface
- Requires at least one free drive bay
- Supported File System Formats: EXT4, NTFS, HFS+, exFAT, Btrfs
- Supports Self-defined Alias Name
- Supports AES 256-bit Encryption for MyArchive Disks

File System

- Internal Disk: EXT4, Btrfs
- External Disk: FAT32, NTFS, ext3, ext4, HFS+, exFAT, Btrfs*

DHCP Server

- Supports multiple IP subnet assignments
- Supports Lease Time, DHCP Reservation

Network

- TCP/IP (IPv4 & IPv6) · Jumbo Frames (MTU)
- VLAN · SMB Multichannel
- EZ-Connect · Wireless Network
- DDNS and EZ-Router · Supports Wake-on-LAN (WOL)
- Supports Wake-on-WAN (WOW)

Network Protocols

- CIFS/SMB, SMB 2.0/3.0, AFP, NFS, FTP (Unicode Supported), TFTP, WebDAV, Rsync, SSH, SFTP, iSCSI, HTTP, HTTPS, Proxy, SNMP, Syslog

Storage Management

- Support Multiple Volumes with Spare Drives
- Volume Type: Single, JBOD, RAID 0, RAID 1, RAID 5, RAID 6, RAID 10
- Support for RAID Level Migration
- Support for RAID Capacity Expansion

Supported Languages

- Deutsch, English, Français, Italiano, Nederlands, Русский, 日本語, 한글, 简体中文, 繁體中文, Ceská, Polski, Svenska, Dansk, Norsk, Suomi, Português, Türkçe, Español, Magyar, ไทย

System Administration

- Support scheduled upgrade ADM & AppLog Type: System Log, Connection Log, File Access Log
- Real-time Online User Monitoring
- Real-time System Monitoring
- User Quotas
- Virtual Drives (ISO Mounting, Maximum 16)
- UPS Support

Network Recycle Bin

- Share folder-based
- Maintains original directory structure and file permission
- One-click restore
- Supports scheduled emptying
- Filtering rules (1.File size 2.File extension)
- Deletion Settings (1.File size 2.File date)

Security

- AES 256-Bit Folder Encryption
- Built-in Hardware Encryption Engine: AS63/64Nimbustor/Lockerstor(G1-G3)/Lockerstor Pro(G1-G2)/Flashstor (G1-G2)series
- Firewall: Helps Prevent Unauthorized Access
- Encrypted Connections: HTTPS, FTP over SSL/TLS, SSH, SFTP, Rsync over SSH
- Alert Notifications: E-mail, SMS, Pushbullet, Pushover, AiMaster
- Supports Let's Encrypt
- Supports Intermediate Certificate
- WORM (Write Once, Read Many)

Dr. ASUSTOR

- Security advice and health records

Snapshot Center

- Btrfs snapshots
- Max: 256 snapshots

Web Center

- Install Apache or Nginx or almost any other web server implementation

Featured Apps

Antivirus (ClamAV)

- Scheduled Scans
- Automatic Virus Definition Updates
- Quarantines Infected Files

ASUSTOR Portal (HDMI™ Local Output)1

- Power Control Settings: Power on, Sleep, Restart and Wake with Remote
- Customizable ASUSTOR Portal Desktop Wallpaper
- Add Shortcuts to Favorite Websites and Resolution Settings
- Max resolution: 1080p (HD)/2160p (4K)²
- URL-Pack connects popular video streaming websites, URL-Pack-Social provides links to a variety of social media platforms

Download Center

- Supports BT(Torrent & Magnet Link), HTTP and FTP Downloads
- Torrent Search
- Customizable Download Schedule
- Bandwidth Control
- RSS Subscription and Automatic Downloading

DataSync Center

- Support Google Drive, Dropbox, Microsoft OneDrive, Yandex, ASUSTOR NAS (EZ Sync), Baidu Wangpan
- Each ADM account is able to individually log into a Cloud Storage account
- Supported backup methods:
 - Sync
 - Directly upload files to Cloud from NAS
 - Directly download files from Cloud to NAS

LooksGood

- Built-in three main video library categories and smart video sorting management
- System administrator can configure video library and editing permissions according to user
- Multimedia conversion function
- Self-defined smart folder for video conversions
- Easy streaming with Chromecast and DLNA

Photo Gallery 3

- Timeline view
- Easily adjustable preview sizes and modes. Includes adjusting by day, month, and year
- Selecting multiple photos to rotate, tag, add to favorites, share and edit photos/videos time and date
- Slideshow viewing mode with playing favorite songs
- Supports a wide range of image formats: JPG/JPEG, GIF, PNG, BMP, TIFF, RAW, HEIC
- View EXIF information and edit photo descriptions
- Easy management of duplicate photos/videos

Cloud Backup Center

- Support Amazon S3, Backblaze B2, Box, Microsoft Azure Blob Storage, Alibaba Cloud, Baidu Cloud, IBM Cloud and Rackspace Cloud Files, WebDAV, SFTP, Google Cloud, hicloud, Lyve Cloud
- Immediate or scheduled backup
- Perform multiple backup tasks and back up multiple accounts

Surveillance Center

- Up to 64 channels in 720p on single live view display
- On-screen camera controls including camera PTZ, manual recordings, take snapshots, configure camera settings and open Maps
- Up to 4 channels of synchronous and non-synchronous playback with audio
- Supported Browsers: Microsoft Edge, Firefox, Chrome
- Event notification supports SMS, E-mail, and mobile push notification
- Role-based access control
- RTSP streaming server (video and audio)
- AiSecure with Push notification
- ONVIF Profile S, T supported
- CMS Lite supports connect up to 256 IP Cameras from 32 NAS
- Two different camera license packages are offered: single channel and 4 channels
- Maximum IP Cam (4 Free Camera Licenses; Additional Licenses to be Purchased)

SoundsGood

- Import Personal/Public Music Collection
- Personal/Public Music Collection Permission Control
- Playlist Editor · ID3 Tag Editor
- Local Speaker Support: HDMI™, USB
- Local Network Audio Output Support: AirPlay Devices

UPnP Media Server

- Offers 2 Different Server Choices: UPnP v2, MiniDLNA
- Supports PS3/Xbox and Other UPnP Compatible Players
- *The supported formats may differ depending on the UPnP client in use

VPN Client

- Supports PPTP, OpenVPN and WireGuard VPN settings
- View Current Connections & Ability to Disconnect Suspicious Connections
- Comprehensive Connection Log

VPN Server

- Supported VPN settings: PPTP, OpenVPN, IPsec/L2TP & WireGuard VPN
- Transmission Package Monitor
- PPTP Authentication: PAP, CHAP, MS CHAP, MS CHAP2
- PPTP Encryption: No MPPE, MPPE (40, 128 bit), Maximum MPPE (128 bit)
- OpenVPN Port Control
- OpenVPN Link Compression
- Supports OpenVPN Configuration Files Importation

ASUSTOR Live

- Multistreaming Including, but not limited to YouTube, Twitch, Facebook, Instagram, Restream or RTMP compatible platforms
- Streaming video save and use

Third party APPs

- Portainer and Docker · VirtualBox
- Plex Media Server · OwnTone

Note:

- ASUSTOR recommends that ASUSTOR Portal be used with a TV with a resolution of 720p or higher.
- Currently, AS63/64/Nimbustor/Nimbustor Gen2/Lockerstor 2&4/
- Lockerstor Gen2/Flashstor series devices are able to provide 4K Output at 60Hz. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc..